

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 100404

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only; T28-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5359)

Set a basalt stone 14x10x5 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face; from which
A Fir 14" dia., bears S.75°E., 17 lks. dist. mkd. ¼ S19 BT
A Fir 12" dia., bears S.89°W., 33 lks. dist. mkd. ¼ S24 BT

GLO resurvey by Lincoln E. Wilkes, Cadastral Engineer; Otto L. Draper and Norman D. Price, Transitmen - Special Instructions dated Dec. 21, 1920 (Surveyed 1927-1928) - (DCSO records Vol. 24 Page(s) 10277-78)

The ¼ cor. established for secs. 19 & 24, which is a basalt stone 10x5x4 ins., above ground, firmly set, marked ¼ on W. face, from which the original bearing trees:
A Fir 18" dia., bears S.75°E., 17 lks. dist. mkd. ¼ S19 BT
A Fir 16" dia., bears S.89°W., 33 lks. dist. mkd. ¼ S24 BT
I now change this cor. to refer to sec. 24 only.
I destroy the markings on bearing tree mkd. for sec. 19 and take new bearing tree as follows:
A Fir 12" dia., bears N.74°W., 19 lks. dist. mkd. ¼ S24 BT