

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 103347-8)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd

T28S R1E

S 6 | S 5

S 7 | S 8

1927

from which

- A fir, 14" dia., bears N.44°E., 12 lks., mkd: T28S R1E S5  
BT.
- A fir, 10" dia., bears S.46°E., 4 lks., mkd: T28S R1E S8  
BT.
- A fir, 12" dia., bears S.72°W., 41 lks., mkd: T28S R1E S7  
BT.
- A fir, 16" dia., bears N.36°W., 32 lks., mkd: T28S R1E S6  
BT.