

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 5 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer,  
Otto L. Draper & Norman D. Price, US Transitmen, under  
Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24  
Page(s) 10354)

-----  
(From S $\frac{1}{4}$  S32, T27-1E) West 1.80 chs  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for  
 $\frac{1}{4}$  cor. of Sec. 5 only, with brass cap marked

$\frac{1}{4}$  S 5  
1928

from which

- A fir, 22" dia., bears S.86°E., 61 lks., mkd:  $\frac{1}{4}$  S5 BT.
- A fir, 60" dia., bears S.83°W., 9 lks., mkd:  $\frac{1}{4}$  S5 BT.