

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer,  
Otto L. Draper & Norman D. Price, US Transitmen, under  
Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24  
Page(s) 10322)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 28, 29, 32, & 33, with brass cap mkd

T28S R1E  
S 29 | S 28  
S 32 | S 33  
1927

from which

- A fir, 14" dia., bears N.78°E., 49 lks., mkd: T28S R1E S28  
BT.
- A fir, 20" dia., bears S.62°E., 28 lks., mkd: T28S R1E S33  
BT.
- A fir, 6" dia., bears S.32°W., 57 lks., mkd: T28S R1E S32  
BT.
- A fir, 24" dia., bears N.72°W., 40 lks., mkd: T28S R1E S29  
BT.