

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10324-5)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd

T28S R1E  
S 20 | S 21  
S 29 | S 28  
1927

from which

- A fir, 12" dia., bears N.63°E., 37 lks., mkd: T28S R1E S21  
BT.
- A fir, 12" dia., bears S.77°E., 42 lks., mkd: T28S R1E S28  
BT.
- A fir, 35" dia., bears S.61°W., 67 lks., mkd: T28S R1E S29  
BT.
- A fir, 12" dia., bears N.82°W., 69 lks., mkd: T28S R1E S20  
BT.