

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10328-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T28S R1E  
S 8 | S 9  
S 17 | S 16  
1927

from which

- A fir, 18" dia., bears N.10½°E., 73 lks., mkd: T28S R1E S9  
BT.
- A fir, 8" dia., bears S.75½°E., 48 lks., mkd: T28S R1E S16  
BT.
- A fir, 10" dia., bears S.81½°W., 9 lks., mkd: T28S R1E S17  
BT.
- A fir, 14" dia., bears N.24°W., 49 lks., mkd: T28S R1E S8  
BT.