

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10331)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T28S R1E

S 5 | S 4

S 8 | S 9

1927

from which

A fir, 24" dia., bears N.64°E., 64 lks., mkd: T28S R1E S4  
BT.

A fir, 10" dia., bears S.25°E., 72 lks., mkd: T28S R1E S9  
BT.

A fir, 12" dia., bears S.58°W., 80 lks., mkd: T28S R1E S8  
BT.

A fir, 12" dia., bears N.5°W., 56 lks., mkd: T28S R1E S5  
BT.