

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 342700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 33 only; T27-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9828 & Vol. 24 Page(s) 10243)

Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces from which
A fir, 24" dia., bears South, 14 lks., mkd: S C ¼ S BT.
A fir, 30" dia., bears North, 62 lks., mkd: S C ¼ S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10265)

The old cor. established for standard ¼ cor. of secs. bears South 113 lks (and West 4.78 chs. (from 1927 ¼ cor.))

I destroy all evidence of this cor.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for standard ¼ sec. cor., with brass cap marked

SC
¼ S 33
1927

from which

A fir, 14" dia., bears N.52½°E., 34 lks., mkd: ¼ S33 SC BT

A fir, 48" dia., bears N.68½°W., 47 lks., mkd: ¼ S33 SC BT
(1/4 Cor. Sec. 4 bears West 1.77 chs.)