

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3 & 3 T29-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol 24 Pages 10256-7 & Vol. 25 Page 10627)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T28S	R1E
S 33	S 34
S 4	S 3
T29S	
1921	

from which

- A cedar, 12" dia., bears N.27°E., 60 lks., mkd: T28S R1E S34 BT.
- A fir, 40" dia., bears S.6°E., 34 lks., mkd: T29S R1E S3 BT.
- A madrona, 8" dia., bears S.37°W., 38 lks., mkd: T29S R1E S4 BT.
- A fir, 30" dia., bears N.23°W., 65 lks., mkd: T28S R1E S33 BT.