

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer,  
Otto L. Draper & Norman D. Price, US Transitmen, under  
Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24  
Page(s) 10319)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T28S R1E  
S 4 | S 3  
S 9 | S 10  
1927

from which

- A fir, 6" dia., bears N.12°E., 13 lks., mkd: T28S R1E S3  
BT.
- A fir, 26" dia., bears S.81°E., 37 lks., mkd: T28S R1E S10  
BT.
- A fir, 18" dia., bears S.3°W., 22 lks., mkd: T28S R1E S9  
BT.
- A fir, 8" dia., bears N.1°W., 30 lks., mkd: T28S R1E S4  
BT.