

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION CC Secs. 3 & 4 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer,  
Otto L. Draper & Norman D. Price, US Transitmen, under  
Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24  
Page(s) 10320-1)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
closing cor. of secs. 3 & 4, with brass cap mkd

T27S R1E  
S 33  
S 4 | S 3  
T28S | R1E  
1927

from which

A fir, 22" dia., bears S.24¼°E., 21 lks., mkd: T28S R1E S3  
CC BT.

A fir, 28" dia., bears S.26¾°W., 16 lks., mkd: T28S R1E S4  
CC BT.

175 lks West from the standard cor. of Secs. 33 & 34