

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34; & 3 T29-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 24 Page 10256 & Vol. 25 Page 10626)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 34}{S\ 3}$
1921

from which

A fir, 16" dia., bears N.81°W., 23 lks., mkd: 1/4 S34 BT.

A madrona, 18" dia., bears S.31°W., 9 lks., mkd: 1/4 S3 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 7/22/1974 - C.S. File 57/2-4

Found - Iron pipe, firmly set, protruding 6" above ground level with brass cap attached mkd: US General Land Office Survey 1/4 S34 S3 1921, from which:

An orig. 16" now 20" D.Fir bears N.81°W., 15.2 ft. well-healed.

A stump hole with fragments of madrone roots bears S.31°W., 5.9 ft. the remainder of the tree is gone.

New BT - A 22" D.Fir bears S.5°W., 26.3 ft. scribed "1/4 S3 CS BT".

This corner lies approx. 75 ft. west of and 30 ft. below an all-weather logging road.