

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Cor. Secs. 34, 35; 2, & 3 T29-01E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 24 Page 10255 & Vol. 25 Pages 10625-6)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T28S | S1E
S 34 | S 35
S 3 | S 2
T29S
1921

from which

- A fir, 10" dia., bears N.76°E., 28 lks., mkd: T28S R1E S35 BT.
- A fir, 14" dia., bears S.73°E., 16 lks., mkd: T29S R1E S2 BT.
- A fir, 8" dia., bears S.41°W., 12 lks., mkd: T29S R1E S3 BT.
- A fir, 10" dia., bears N.60°W., 9 lks., mkd: T28S R1E S34 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - Terrie Plouff - July 15, 1981 - C.S. File 61/27-21

-
- Found - Orig. GLO Brass Cap firmly set, protruding 8" out of the ground, mkd T28S R1E S34 S35 T29S S3 S2 1921
- 14" Fir (Orig. 10") bears N.76°E., 18.5 ft., with well healed blaze.
 - 18" Fir (Orig. 14") bears S.73°E., 11.0 ft., (rec 10.6 ft.), with well healed blaze.
 - 8" snag (Orig. 8" Fir), 14 ft. tall bears S.41°W., 7.9 ft., with well healed blaze.
 - 14" Fir (Orig. 10") bears N.60°W., 5.9 ft., with well healed blaze.

New BT - 10" Fir bears S.21°W., 10.6 ft., scribed T29S R1E S3 CS BT, in a double blaze.

NOTE - All BTs tagged with DCSO BT tags.