

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10296)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd

T28S R1E  
S 27|S 26  
S 34|S 35  
1927

from which

- A fir, 20" dia., bears N.22°E., 47 lks., mkd: T28S R1E S26 BT.
- A fir, 8" dia., bears S.36½°E., 40 lks., mkd: T28S R1E S35 BT.
- A fir, 10" dia., bears S.11½°W., 103 lks., mkd: T28S R1E S34 BT.
- A fir, 36" dia., bears N.88°W., 37 lks., mkd: T28S R1EE S27 BT.