

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 2, T29-01E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 24 Page 10255 & Vol. 25 Page 10625)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 35}{S\ 2}$
1921

from which

A fir, 30" dia., bears N.4°E., 25 lks., mkd: 1/4 S35 BT.

A Laurel, 7" dia., bears S.83°E., 11 lks., mkd: 1/4 S2 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Gary Commons - 7/29/1974 - C.S. File 57/2-6

Found - 1" IP with 1921 U.S. GLO brass cap properly mkd. leaning and loosely supported in a mound of rocks. Due to inconsistencies found in the measurements from the brass cap at its present location and the fact that the mound of rocks is not mentioned in the orig. field notes, we remove the brass cap and reset it at the following measurements from the remains of the two orig. bearing trees:

An orig. 30" Fir, now a 36" Fir snag bears N.4°E., 16.5 ft. we open and find good scribing "5" on a rotten face

An orig. 7" now 9" Madrone bears N.83°E., 7.3 ft. (rec. S.83°E., 7.3 ft.). We find some illegible scribe marks on an open blaze that has been defaced some years earlier.

The brass cap is now set 16" in the ground to solid rock and supported by a mound of stone 2 ft. wide by 1 ft. high, from which we mark the following

New BTs- A 14" D.Fir bears N.50°W., 28.2 ft. scribed "1/4 S35 CS BT.

A 9" D.Fir bears S.13 1/2°W., 27.0 ft. scribed "1/4 S2 CS BT"