

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10307)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S \ 2}{S \ 11}$
1927

from which

A fir, 16" dia., bears N.58°E., 57 lks., mkd: 1/4 S2 BT.

A pine, 66" dia., bears S.65°E., 21 lks., mkd: 1/4 S11 BT.

BLM Mineral Survey 1008 A&B by Richard C. Skinner, Mineral Surveyor, survey under order dated June 30, 1992, Survey of Mineral Claims of: Anna Lu Rannells, Surveyed July/Aug. 1992 - (DCSO records Vol. 50 Page(s) 18932)

The 1/4 sec. cor, of secs, 2 and 11, T28S R1E WM monumented with a 1" dia, iron post 10" above the ground, firmly set, with a 2 1/2" dia, GLO brass cap properly marked, from which the original bearing trees are at record measurements and in good condition,