

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 542700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35 only; T27-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9830 & Vol. 24 Page(s) 10244)

Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces from which
A pine, 14" dia., bears S.65°W., 27 lks., mkd: S C ¼ S BT.
A pine, 12" dia., bears N.43°E., 30 lks., mkd: S C ¼ S BT.
Peak of Quartz Mountain S.25°E., say 20 chains dist.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10268)

The old cor. established for standard ¼ cor. of sec. 35, bears (West 6.47 chs and) S.2½°E., 126 lks.
I destroy all evidence of this cor.
335 ft. below spur
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for standard ¼ sec. cor., with brass cap marked
SC
¼ S 35
1927
from which
A fir, 24" dia., bears N.81°E., 95 lks., mkd: ¼ S35 SC BT.
A pine, 12" dia., bears N.85°W., 53 lks., mkd: ¼ S35 SC BT
(1/4 cor. sec. 2 bears West 1.57 chs.)