

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10288-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T28S R1E  
S 14 | S 13  
S 23 | S 24  
1927

from which

- A fir, 26" dia., bears N.45°E., 33 lks., mkd: T28S R1E S13 BT.
- A fir, 7" dia., bears S.60°E., 31 lks., mkd: T28S R1E S24 BT.
- A fir, 7" dia., bears S.77°W., 40 lks., mkd: T28S R1E S23 BT.
- A fir, 16" dia., bears N.47½°W., 69 lks., mkd: T28S R1E S14 BT.