

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10293)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T28S R1E
S 2|S 1
S 11|S 12
1927

from which

- A fir, 16" dia., bears N.55¼°E., 17 lks., mkd: T28S R1E S1 BT.
- A fir, 20" dia., bears S.41½°E., 8 lks., mkd: T28S R1E S12 BT.
- A pine, 48" dia., bears S.61¼°W., 39 lks., mkd: T28S R1E S11 BT.
- A pine, 50" dia., bears N.22°W., 45 lks., mkd: T28S R1E S2 BT.

Ronald Quimby, L.S. #1654 - Darrel Jones - Oct. 12, 1984 - C.S. 58/290-7

Found - 2" iron pipe with brass cap marked "US General Land Office 2|1
11|12 192" firmly set protruding 4" out of the ground. (1927 survey)

48" pine bears S.59°W., 25.5 ft. (Rec. S.61¼°W., 25.7 ft.) with visible scribe "S11 BT".

- New -
- A 5/8"x30" iron rod with plastic cap SURVEYING SERVICE INC." bears N.45°E., 12.0 ft.
 - A 5/8"x30" iron rod with plastic cap SURVEYING SERVICE INC." bears S.45°E., 16.7 ft.
 - A 5/8"x30" iron rod with plastic cap SURVEYING SERVICE INC." bears S.45°W., 10.5 ft.
 - A 5/8"x30" iron rod with plastic cap SURVEYING SERVICE INC." bears N.45°W., 13.0 ft.

Note - Cor. falls in large clear cup unit.
Compass decl. 19½°E.