TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 602700

PRIMARY CORNER DESCRIPTION CC Secs. 35 & 36 only; T27-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9830 & Vol. 24 Page(s) 10245)

Set post 48x4" firmly in the ground for stand. cor. to secs. 35 & 36 marked S C T 27 S R 1 E on N S 36 on E and S 35 on W faces with 1 notch on E & 5 on W edges from which

A pine, 30" dia., bears N.40°E., 27 lks., mkd: T27S R1E S36 BT.

A chinquapin, 8" dia., bears N.50°W., 31 lks., mkd: T27S R1E S35 BT.

A pine, 24" dia., bears S.35°W., 33 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10269)

The old cor. established for standard cor. of secs. 35 & 36, bears (West 5.66 chs and) S.48¾°W., 210 lks.
I destroy all evidence of this cor.
85 ft. above branch
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 35 & 36, with brass cap mkd

S C
T27S | R1E
S 35 | S 36
T28S R1E
1927

from which

A pine, 16" dia., bears N.59°E., 59 lks., mkd: T27S R1E S36 SC BT.

A fir, 24" dia., bears N.41°W., 27 lks., mkd: T27S R1E S35 SC BT.

East 1.67 chs from Cor. Secs. 1 & 2