

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 642700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 36 only; T27-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9831 & Vol. 24 Page(s) 10245)

-----  
Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces, from which  
A fir, 20" dia., bears N.70°W., 28 lks., mkd: S C ¼ S BT.  
A fir, 8" dia., bears S.50°E., 182 lks., mkd: S C ¼ S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10269-70)

-----  
The old cor. established for standard ¼ cor. of sec. 36 bears (West 7.65 chs and) S.9½°W., 140 lks.  
I destroy all evidence of this cor.  
A fir, 60" dia., for standard ¼ sec. cor. I mark SC ¼ S36 on N side; from which  
A fir, 30" dia., bears N.81°E., 104 lks., mkd: ¼ S36 SC BT  
A fir, 5" dia., bears N.60°W., 21 lks., mkd: ¼ S36 SC BT.  
The standard ¼ Cor. of sec. 1 bears West 1.67 chs.