

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 36; 30 & 31 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, USCE, under Special Instr.  
dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10385-6)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 25, 30, 31, & 36, with brass cap mkd

T28S  
R1E|R2E  
S 25|S 30  
S 36|S 31  
1927

from which

- A pine, 30" dia., bears N.74°E., 56 lks., mkd: T28S R2E  
S30 BT.
- A pine, 36" dia., bears S.62°E., 54 lks., mkd: T28S R2E  
S31 BT.
- A pine, 42" dia., bears S.45°W., 87 lks., mkd: T28S R1E  
S36 BT.
- A pine, 30" dia., bears N.52°W., 48 lks., mkd: T28S R1E  
S25 BT.