

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13, 7 & 18 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, USCE, under Special Instr.  
dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10389)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T28S  
R1E|R2E  
S 12|S 7  
S 13|S 18  
1927

from which

- A fir, 20" dia., bears N.33°E., 53 lks., mkd: T28S R2E S7  
BT.
- A fir, 24" dia., bears S.13½°E., 43 lks., mkd: T28S R2E  
S18 BT.
- A cedar, 16" dia., bears S.35°W., 19 lks., mkd: T28S R1E  
S13 BT.
- A fir, 12" dia., bears N.15°W., 30 lks., mkd: T28S R1E S12  
BT.