

TOWNSHIP 28 RANGE 01E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T28-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, USCE, under Special Instr.  
dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10390-1)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T28S  
R1E R2E  
S 1 | S 6  
S 12 | S 7  
1927

from which

- A cedar, 12" dia., bears N.57½°E., 25 lks., mkd: T28S R2E  
S6 BT.
- A pine, 36" dia., bears S.19°E., 25 lks., mkd: T28S R2E S7  
BT.
- A pine, 30" dia., bears S.58°W., 77 lks., mkd: T28S R1E  
S12 BT.
- A cedar, 12" dia., bears N.34°W., 49 lks., mkd: T28S R1E  
S1 BT.