

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. S31, T28-1; NW Cor. S6, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5367)

Set a basalt stone 15x12x5 ins., 10" in ground for cor. of T28 and 29S., R1 and 2 W. marked with 6 notches on each edge; from which

- A Fir 16" dia., bears N.60°E., 55 lks. dist. mkd. T28S R1W S31 BT.
- A Fir 24" dia., bears S.70°E., 50 lks. dist. mkd. T29S R1W S6 BT.
- A Pine 10" dia., bears S.55°W., 13 lks. dist. mkd. T29S R2W S1 BT.
- A Fir 30" dia., bears N.65°W., 12 lks. dist. mkd. T28S R2W S36 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6213)

(From the NE. Cor. Sec. 1, T29S R2W, N.35°31'E., 55.16 chs. dist.) The old cor. to Tps. 28 and 29 S., Rs. 1 and 2 W., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I now change this cor. to refer to T28S R1W only and obliterate all markings on old SE.; SW.; and NW. bearing trees.

Tied and used corner in GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6145)