

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5368)

Set a basalt stone 12x8x6 ins., 8" in ground for ¼ sec. cor. marked ¼ on W. face; from which

A Laurel 14" dia., bears S.80°E., 35 lks. dist. mkd. ¼ S31 BT.

A Maple 16" dia., bears N.35°W., 25 lks. dist. mkd. ¼ S36 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5480)

The ¼ sec. cor. established for secs. 31 and 36, which is a basalt stone, 8x6x5 ins. above ground, firmly set, mkd. ¼ on W. face. Hereafter, this cor. will refer to sec. 31 only: I obliterate the marks on W. face and remark the stone ¼ S31 on E. face, from which

A Fir 4" dia., bears N.19°E., 32 lks. dist. mkd. ¼ S31 BT. New Bearing tree.

A Laurel 14" dia., bears S.80°E., 35 lks. dist. mkd. ¼ S31 BT. Old bearing tree, now dead.

A Fir 36" dia., bears S.39°E., 41 lks. dist. mkd. ¼ S31 BT. New Bearing tree.

A Laurel 16" dia., bears N.35°W., 25 lks. dist., I obliterate the marks on this tree.