

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5369)

-
- Set a basalt stone 15x10x5 ins., 10" in ground for cor. of secs. 19, 24, 25 and 30, marked with 2 notches on S. and 4 notches on N. edges; from which
- A Dogwood 12" dia., bears N.40°E., 33 lks. dist. mkd. T28S R1W S19 BT.
 - A Dogwood 12" dia., bears S.40°E., 63 lks. dist. mkd. T28S R1W S30 BT.
 - A Fir 18" dia., bears S.72°W., 53 lks. dist. mkd. T28S R2W S25 BT.
 - A Cedar 14" dia., bears NW. 40 lks. dist. mkd. T28S R2W S24 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5483)

-
- The cor. established for secs. 19, 24, 25 and 30, which is a basalt stone 10x5x5 ins. above ground, firmly set, mkd. with 2 notches on S. and 4 notches on N. edge. Hereafter, this cor. will refer to secs. 19 and 30 only; I mark the cor. stone S19 on NE.; and S30 on SE. face, from which
- A Chinquapin 12" dia., bears N.40°E., 31 lks. dist., old bearing tree, now dead.
 - A Fir 36" dia., bears N.52°E., 85 lks. dist. mkd. T28S R1W S30 BT. Old BT.
 - A Chinquapin 12" dia., bears S.53°E., 33 lks. dist. mkd. T28S R1W S30 BT. Old BT.
 - A Fir 18" dia., bears S.72°W., 53 lks. dist., I obliterate the marks on this old bearing tree.
 - A Cedar 14" dia., bears N.45°W., 40 lks. dist., I obliterate the marks on this old bearing tree.