

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5369-70)

Set a basalt stone 15x12x8 ins., 10" in ground for ¼ sec. cor., marked ¼ on W. face; from which
A Fir 10" dia., bears S.30°E., 28 lks. dist. mkd. ¼ S19 BT
A Fir 14" dia., bears N.49°W., 14 lks. dist. mkd. ¼ S24 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5484-85)

The ¼ sec. cor., established for secs. 19 and 24, which is a basalt stone 12x8x5 ins. above ground, firmly set, marked ¼ on W. face. Hereafter this cor. will refer to sec. 19 only. I obliterate the marks on W. face of cor. stone, and mark it ¼ S19 on E. face,
from which
A Hemlock 10" dia., bears N.66°E., 24 lks. dist. mkd. ¼ S19. New BT.
A Hemlock 10" dia., bears S.26°E., 48 lks. dist., mkd. ¼ S19 BT. Old BT.
A Hemlock 14" dia., bears N.49°W., 14 lks. dist. I obliterate marks on this old bearing tree.