

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 100436

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T28-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 13 Page(s) 5486-87)

-----  
Set an Iron post 3 ft. long, 2' dia., 27" in the ground for cor. of secs. 12 & 13 only, with brass cap mkd.

T28S		T28S
<u>S 12</u>		R1W
S 13		
R2W		S18
1923		

from which

A Fir 60" dia., bears S.34°W., 52 lks. dist. mkd. T28S R2W S13 BT.

A Yew 7" dia., bears N.41°W., 20 lks. dist. mkd. T28S R2W S12 BT.

Douglas County Surveyors Office - Gary Langlitz & Karen Cheney, crew - Sept. 21, 1976 - C.S. File 59/24-15

-----  
Found - Orig. 1923 SW. BT, 60" now 64" Fir, alive and well healed.

The 1923 corner monument and NW. BT, have been lost due to logging activity.

At the true corner location as determined by the record measurements from the orig. SW. bearing tree:

We set a 1" x 30" I. Pipe 28" in the ground with brass cap attached mkd.: Douglas Co. Surveyor

T 28 S			
R			R
2	<u>S 12</u>		S 18 1
W	S 13		W
1976			

from which

The original SW. BT bears S.34°W., 34.3 ft.

New BT, a 16" G.Fir bears N.10°E., 34.2 ft. scribed "T28S R1W S18 CS BT" on a double blaze.