

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5367)

Set a basalt stone 15x12x7 ins., 10" in ground for ¼ sec. cor. marked ¼ on N. face; from which
A Fir 18" dia., bears S.75°W., 54 lks. dist. mkd. ¼ S6 BT.
A Fir 14" dia., bears N.45°W., 46 lks. dist. mkd. ¼ S31 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6146)

Intersect the old ¼ sec. cor., which is a basalt stone, 5x12x7 ins. above ground, firmly set, marked ¼ on N. face, and witnessed as described by the surveyor general. I obliterate the marks on the old SW. bearing tree and change this cor. to refer to sec. 31 only, and mark a new bearing tree as follows:
A Cedar 18" dia., bears N.33°E., 55 lks. dist. mkd. ¼ S31 BT. (New BT)
A Fir 18" dia., bears N.45°W., 46 lks. dist. mkd. ¼ S31 BT. (Old BT)