

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5416)

-----  
Set a basalt stone 15x12x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 24" dia., bears SE., 55 lks., mkd: ¼ S19 BT.  
A fir, 14" dia., bears N.30°W., 18 lks., mkd: ¼ S18 BT.

Douglas Co. Surveyors Office - Karen Reed - Terrie Plouff - Aug. 4, 1982 - C.S. File 62/1-3

-----  
Found - A 15"x12"x5" basalt stone buried 6" in the ground. No visible marks as recorded in 1902 survey at record bearing and distance from NW BT.  
An orig. 14" fir, now a 22" Hemlock bears N.30°W., 11.9 ft. with partially healed single blaze. Visible scribe " C "  
An orig. 24" fir, now a 43" bears S.48½°E., 36.3 ft. (Rec. SE.) with previously chopped single blaze now healed over.  
Set - Since no markings were found on stone, I pulled record distances from both original BTs at this point the bearing for the NW tree was good. Holding this position I set 1½" x 30" iron pipe with brass cap stamped  
"Douglas Co. Surveyor T28S R1W ¼ S18/S19 1982" protruding 6" above ground with 1.5 ft dia mound of stone. Placed original stone south side of cap beneath surface. This position falls on the found stone.  
New BTs- A 7" hemlock bears N.29½°E., 25.3 ft. scribed "¼ S18 CS BT" in a double blaze.  
A 14" dia. Hemlock bears S.86½°W., 23.0 ft. scribed "¼ S19 CS BT" in a double blaze.  
Corner falls on a SW slope approx. 26°. Sketch in C.S. file.