

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5418-9)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A hemlock, 24" dia., bears N.44°E., 25 lks., mkd: ¼ S7 BT.
A hemlock, 24" dia., bears S.21°W., 24 lks., mkd: ¼ S18 BT

Maurice E. Farr, USFS - Leonard Herzstein, Party Chief - Randy Lopez, Witness - 1983 & 8/14/1985 - C.S. File 62/26-2

I searched for and did not find original corner stone. This area was clearcut in 1983. The stone was not found by district personnel prior to the timber cutting. In my visit to the site in July, 1983, the corner point was covered by freshly fallen and bucked timber. In August, 1985, the area was covered with slash and had obviously been disturbed. Record bearing tree distances from center of trees wouldn't intersect, but distances measured from the blazed faces match the record bearings.

Found - Orig. BTs established by Homer D. Angell, Deputy Surveyor, in 1902:

- A 28" W.Fir stump, N.44°E., 16.5 ft. to face, 17.4 ft. to 60d nail set in center of stump. (Rec. Hemlock, 16.5 ft.) with scribe marks "S7 BT" visible on single blaze which I opened.
- A 40" D.Fir stump, S.21°W., 15.8 ft. to face, 17.0 ft. to 60d nail set in center of stump. (Rec. Hemlock, 15.8 ft.) with healed single blaze.

Set - At the intersection of the record bearings and distances from the blazed faces, I SET a 2¼" outside dia. iron pipe, 30" long, set 12" in the ground with a 4 ft dia. mound of stone to the top with a brass cap marked "T28S R1W ¼ S7 S18 LS 1181 1985 inside the iron pipe I placed a ½" wire rope, 12" long with bell on the base as a memorial.

I set a 6 ft. steel fence post, east, 3.0 ft. driven 1.5 ft. in the ground as a guard post with forest sign #54-4 attached.

New BTs- In 1983, an 8" hemlock, N.10°E., 76.7 ft. scribed "¼ S7 BT" on a single blaze.

In 1985 a 5" hemlock, S.45¼°E., 86.2 ft. scribed "¼ S18 BT" on a single blaze with a ¾" brass washer, stamped "LS 1181" nailed flush to base of blaze.

continued next page

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - Corner is 2 ft. south of draw which drains N.70°W.,
and 60 ft. south of the timber line in unit #14
of the Red Idiot Timber Sale. Corner is approx.
300 ft. north of Forest Rd. #2792.