

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5421)

-----

Set a basalt stone 15x12x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 14" dia., bears N.25°E., 30 lks., mkd: ¼ S6 BT.

A fir, 20" dia., bears S.10°W., 20 lks., mkd: ¼ S7 BT.

Glenn Baughman - For: US Forest Service - Nov. 21, 1978 - C.S. File 58/176-13

-----

Found - 8"x8"x10" high stone with 5 notches on south face.  
20" D.Fir, 7 foot high stump with good healed blaze and "BT" tag bearing N.52°E., 31.4 ft.

36" D.Fir, 1 foot high stump with partial healed and "BT" tag bearing S.81°E., 33.5 ft.

I scribed-26" D.Fir bears N.72°E., 51.1 ft. scribed "T28S R1W S6 BT".

48" D.Fir bears S.14°E., 100.0 ft. scribed "T28S R1W S7 BT".