

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4767)

Set post 44x4 ins. firmly in the ground for stan. $\frac{1}{4}$ sec. cor.
marked S C on N. and S. faces, from which
A Fir 36" dia., bears N.62°E., 9 lks. dist. mkd. S C $\frac{1}{4}$ S
BT.
A Fir 10" dia., bears S.10°E., 31 lks. dist. mkd. S C $\frac{1}{4}$ S
BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4778)

(35.62 chs.)
Old $\frac{1}{4}$ sec. cor. on line which I destroy.
(40.00 chs.)
Set basalt stone 12x10x8 ins., 8" in ground for stan. $\frac{1}{4}$ sec.
cor. marked S C $\frac{1}{4}$ on N. face, from which
A Fir 30" dia., bears N.10°E., 55 lks. dist. mkd. S C $\frac{1}{4}$
S31 BT.
A Fir 20" dia., bears S.15°W., 8 lks. dist. mkd. S C $\frac{1}{4}$ S6
BT.

Dennis Gaylord, U.S. Forest Service (Deputized by the DCSO)
Wit: Randal Lopez - Jan. 12, 1978 - C.S. File 59/46-1

Found - Corner stone called for in GLO notes is gone.
A 19" Fir stump bears S.21°W., 5.28 ft. (Rec.
S.15°W., 5.28 ft.) Scribing visible on partly
healed blaze " $\frac{1}{4}$ S6 BT".
A 40" Fir stump bears N.4°E., 36.3 ft. (Rec.
N.10°E., 36.3 ft.) Has a healed scar.
Using the record BT distances as reference, I chain from BT
stumps and SET a 2 $\frac{1}{2}$ " brass cap on a 1" I.P. stamped:
County Surveyors Office 1978
T 27 S R 1 W
 $\frac{1}{4}$ S 31
S. C.

New Accessories:

- A 15" W.Fir bears S.55°W., 86.7 ft. scribed " $\frac{1}{4}$ S31
CS BT" on a double blaze.
- A point of rock 10 ft. x 6 ft. x 4 ft. above ground.
On the E.S.E. face, I mark "X BR" 1 ft. above
ground. "X" mark bears N.24°E., 14.0 ft.
- A 13" W.Fir bears S.74 $\frac{1}{2}$ °E., 121.0 ft. scribed $\frac{1}{4}$ S31
CS BT" on a double blaze.

(Cont. Next Page)

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 141700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Placed County BT signs on 2 stumps and 2 new BTs.
Corner located in SW. corner of a clearcut unit. This is a
standard cor. on the 6th standard parallel South.