

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5417)

-----

Set a basalt stone 12x10x8", in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edges, from which

- A fir, 12" dia. bears N.26°E., 25 lks. mkd: T28S R1W S8 BT
- A hemlock, 18" dia., bears S.40°E., 40 lks., mkd: T28S R1W S17 BT.
- A hemlock, 12" dia., bears S.54°W., 154 lks., mkd: T28S R1W S18 BT.
- A fir, 18" dia. bears N.40°W., 63 lks. mkd: T28S R1W S7 BT

Douglas Co. Surveyors Office - Gregory E. Quibell - Gary L Langlitz - 6/24/1975 - C.S. File 57/30-16

-----

- Found - Basalt stone as described in orig notes. From which:
- An orig. 12" now 18" Fir bears N.31°E., 15.7 ft. (Rec. N.26°E., 16.5 ft.) Alive with well healed blazes.
  - An orig. 18" now 36" Hemlock bears S.40°E., 26.4 ft., alive with scribe marks visible in unhealed blaze.
  - An orig. 12" now 22" Hemlock bears S.54°W., 101.6 ft., alive with rotted face showing through unhealed blaze.
  - An orig. 18" now 39" Fir bears N.40°W., 41.6 ft. Scribe marks facing south are visible in unhealed blaze.

Set - At the Cor. point we set 1" X 30" iron pipe with brass cap marked COUNTY SURVEYORS OFFICE T28S

1975	S 7   S 8
	S 18   S 17
	R1W

We place orig. stone along south side of brass cap.