

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only (north)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5421-22)

Set a basalt stone 15x6x6 ins., 10" in ground for closing cor. for secs. 5 and 6, marked C C on S. and 5 grooves on E. and 1 groove on W. faces; from which
A Fir 12" dia., bears S.22°E., 45 lks. dist. mkd. T28S R1W S5 BT.
A Fir 14" dia., bears S.75°W., 37 lks. dist. mkd. T28S R1W S6 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 16, 1969 - C.S. File 54/94-45

Found - No trace of corner stone.
12" now 26" D.Fir, S.22°W., 24.4 ft. (Rec. S.22°E., 29.7 ft.), opened for scribe.
14" now 29" D.Fir S.75°E., 29.7 ft. (Rec. S.75°W., 24.4 ft.), shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T27S R1W CC S 31
T28S 1969 S 6 | S 5

Bearing trees OK and tagged.
Record dist. betw. corners 13.2 ft., I find to be 15.5 ft.