

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5420)

Set a basalt stone 12x10x6", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
A hemlock, 10" dia., bears N.25°E., 16 lks., mkd: 1/4 S5 BT.
A pine, 10" dia., bears S.22°W., 57 lks., mkd: 1/4 S8 BT.

James N. Landrum, LS 2024 - For: US Forest Service - March 29, 1984 - ~~C.S. File 59/30~~ moved to C.S. File 62/50-13

REFERENCED OUT CORNER REPORT ONLY

Found - Basalt stone 10"x4"x6" high (rec. 12"x10"x6") No marks visible (Set by Angell, 1902)
14" hemlock, N.30°E., 10.6 ft. (Rec N.25°E.) with a healed blaze. Painted 6" red band around tree.
Pine snag, 18", S.22°W., 36.7 ft (rec. 37.6 ft) with a healed blaze. Painted 6" red band around tree.
No monument set at this time. Monument should be set after timber unit is cut.
Set - 40d nail in base of 10" hemlock. Nail head bears S.79 1/2°E. 10.0 ft Painted 6" red band around tree.
40d nail in base of 18" hemlock. Nail head bears S.28 1/2°W. 8.8 ft. Painted 6" red band around tree.
Set guard post with 54-4 sign, N.60°W., 1.9 ft.
Corner falls ± 200 ft. inside proposed clear cut.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - March 23, 1988 - C.S. File 62/50

Found - A 10"x10"x 4" stone, with no marks, firmly set and protruding 3" above ground. Stone recorded as a 10"x4"x6" in 1984 and originally as a 12"x10"x6".
10" now 16" dia. 6 ft. high hemlock stump with a fully healed single blaze bears N.30°E., 10.6 ft. Orig. BT, agrees with 1984 ren.
10" pine now 16" dia. 6 ft. high stump (species of tree may be wrong bark looks similar to W.Fir) has a fully healed single blaze, opened and scribing found "4S" bears S.22°W., 36.7 ft. Orig. BT
18" now 18" dia. 5 ft. high Hemlock stump with nail in base on North side, bears S.32°W., 8.8 ft. to head of nail. (Record, S.28 1/2°W., 8.8 ft.) per 1984 Ren.

continued next page

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

10" Hemlock, uprooted and out of ground (rec. S.79½°E., 10.0 ft.) Metal witness post and sign bears N.50°W., 1.9 ft. (Rec. N.60°W., 1.9 ft.) Per. 1984 Ren.

Set - Position of stone is referenced and a 2 3/8" brass cap on a 1"x32" long iron pipe set at referenced position, protrudes 6" above ground. Cap is mkd. "Douglas County Surveyors T28S R1W ¼ S 5 1988 Office" S 8

Stone is set along northeast edge of BC/IP flush with ground.

New - 20" dia. 14" high D. fir stump with a boat spike stamped "BO 1" set through a bearing tree tag into top of stomp near center. Spike bears N.89°E., 10.6 ft.

15" dia. 12" high Hemlock stump with a boat spike stamped "BO 2" set through a bearing tree tag into top of stump near center. Boat spike bears N.40°W., 43.5 ft.

Corner lies approx. 300 ft. west of east edge of clear cut and approx. 250 ft. east of landing at end of spur road.