

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for 32 only, T27-1 \*

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4768)

-----  
Set post 40x4 ins. firmly in the ground for stan. ¼ sec. cor.  
marked S C on N. and S. faces, from which  
A Fir 26" dia., bears N.35°W., 102 lks. dist. mkd. S C ¼  
S BT.  
A Fir 5" dia., bears S.10°W., 29 lks. dist. mkd. S C ¼ S  
BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4777)

-----  
(35.98 chs.)  
Old ¼ sec. cor. on line which I destroy.  
(40.00 chs.)  
A Basalt stone 18x12x6 ins., 14" in the ground for stan. ¼  
sec. cor. marked S C ¼ on N. face, from which  
A Fir 18" dia., bears S.32°W., 15 lks. dist. mkd. S C ¼ S5  
BT.  
A Fir 16" dia., bears NW. 14 lks. dist. mkd. S C ¼ S32 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -  
Dec. 12, 1969 - C.S. File 54/94-86

-----  
Found - 18x12x6 stone, firmly in ground mkd. "¼" on N. face.  
18" now 34" D.Fir S.32°W., 9.9 ft. opened for scribe  
"¼".  
16" D.Fir now snag, N.45°W., 9.2 ft., scribe  
visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 27 S R 1 W  
¼ S 32  
T 28 S  
1969

New BTs- 30" D.Fir N.40°W., 22.5 ft. mkd. ¼ S32 CS BT.  
28" D.Fir N.51°E., 21.7 ft. mkd. ¼ S32 CS BT.

I opened and destroyed scribing of SW. BT as this corner does  
not refer to section 5.

\* This is a common corner for S32/S5 per Fritz Ingram's GIS  
calculations 4/93