

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 and 33 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5365-66)

-
- Set a basalt stone 15x10x5 ins., 10" in ground for cor. of secs. 4, 5, 32 and 33 marked with 4 notches on E. and 2 notches on W. edges; from which
- A Chinquapin 12" dia., bears NE. 7 lks. dist. mkd. T28S R1W S33 BT.
 - A Fir 24" dia., bears S.15°E., 19 lks. dist. mkd. T29S R1W S4 BT.
 - A Laurel 12" dia., bears S.24°W., 33 lks. dist. mkd. T29S R1W S5 BT.
 - A Fir 12" dia., bears N.19°W., 29 lks. dist. mkd. T28S R1W S32 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6148)

-
- Intersect the old cor. of secs. 4, 5, 32 and 33, which is a basalt stone 5x10x5 ins. above ground, firmly set, marked with 4 notches on E. and 2 notches on W. edge, from which
- A Chinquapin 12" dia., bears N.45°E., 7 lks. dist. mkd. T28S R1W S33 BT. (Old BT)
 - A Fir 14" dia., bears N.19°W., 29 lks. dist. mkd. T28S R1W S32 BT. (Old BT)
- I obliterate marks on the old SE. and SW. bearing trees and hereafter this cor. will refer to secs. 32 and 33 only.