

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5407)

-----

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A pine, 12" dia., bears N.50°E., 20 lks., mkd: ¼ S9 BT.
- A fir, 12" dia., bears N.55°W., 8 lks., mkd: ¼ S8 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - 9/3/1971 - C.S. File 54/94-110

-----

Found - Stone, firmly set at corner mkd: "¼" on West face.  
12" Pine, now down, N.50°E., 13.2 ft. shows scar.  
12" now 14" Fir, N.55°W., 5.3 ft. shows good scar.

Set - Brass cap alongside stone mkd:

COUNTY SURVEYORS      T28S   R1W  
OFFICE 1971                    ¼    S8|S9

New BT - 8" Hemlock S.22°E., 12.8 ft. scribed "¼ S9 CS BT"