

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 16 & 21 (WC)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5405)

Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 14" dia., bears N.50°E., 10 lks., mkd: ¼ S16 BT.
A fir, 14" dia., bears S.15°W., 15 lks., mkd: ¼ S21 BT.

Bruce Shaner - For: US Forest Service - Aug. 24, 1964 - C.S. 51/259

Found - Basalt stone, from which a:
18" D.Fir BT with scribed visible bears S.15°W., 9.9 ft.
18" D.Fir BT with old face bears N.50°E., 6.6 ft.
New BT - 16" D.Fir I scribed "¼S S21 BT" bears S.86°E., 84.0 ft.

Douglas Co. Surveyors Office - John Powell - Frank Jones & J. Brady - Oct. 27, 1967 - C.S. File 54/26-12

Found - Orig. 18" D.Fir, now stump, S.15°W., 9.9 ft. Tree has been opened, scribe marks visible.
Orig. 18" D.Fir, now stump, N.50°E., 6.6 ft. shows good scar.
16" now 16" D.Fir S.86°E., 84.0 ft pitched over face
As corner falls in new road, set witness corner 50.0 ft East.
Set - Brass cap at wit cor. mkd:

COUNTY SURVEYORS T28S R1W
OFFICE WIT COR 50' WEST TO
1967 ¼ S 16
S 21

New BTs- 15" D.Fir S.16°W., 11.6 ft. mkd: WC ¼ S21 CS BT.
11" D.Fir N.54°E., 10.8 ft. mkd: WC ¼ S16 CS BT.
Other BT to orig. corner becomes:
16" D.Fir S.80°E., 35.6 ft. scribed ¼ S21 BT.

Note - This corner will fall approx. 70.0 ft. East of road which is not built yet. Road Station 171+36.