

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5396-7)

Set a basalt stone 15x10x6", 10" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notches on E edges, from which

- A fir, 14" dia., bears N.57°E., 103 lks., mkd: T28S R1W S10 BT.
- A fir, 12" dia. bears S.24°E., 53 lks mkd: T28S R1W S15 BT
- A fir, 40" dia. bears S.34°W., 84 lks mkd: T28S R1W S16 BT
- A fir, 8" dia., bears N.57°W., 16 lks. mkd: T28S R1W S9 BT

Douglas Co. Surveyors Office - John Powell - W. Penley & J Heritage - 9/3/1971 - C.S. File 54/94-111

Found - 15x10x6 Stone, 4 notches South, 3 notches East, firmly set in ground.

- 14" now 28" Fir, N.59°E. (Rec.N57°E.) 68.0 ft.
- 12" Fir, now down, S.24°E. 35.0 ft., found face, no scribing.
- 40", now 48" Fir, S.34°W. 62.4 ft. (Rec.55.4) opened earlier for scribe "8S"

No trace of NW BT.

Set - Brass Cap alongside N. Side of Stone mkd:
COUNTY SURVEYORS OFFICE

T28S R1W
S 9 | S 10
S 16 | S 15
1971

New BTs- 7" D.Fir N.86°W. 10.7 ft. scribed "T28S R1W S9 CS BT".

13" D.Fir S.58°E. 19.4 ft. scribed "T28S R1W S15 CS BT".