

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5398)

-----

Set a basalt stone 15x10x5", 10" in the ground for cor. of secs. 3, 4, 9, & 10 mkd with 5 notches on S & 3 notches on E edges, from which

    A cedar, 12" dia., bears N.41°E., 22 lks., mkd: T28S R1W S3 BT.

    A fir, 14" dia. bears S.50°E., 33 lks mkd: T28S R1W S10 BT

    A fir, 12" dia., bears SW., 39 lks., mkd: T28S R1W S9 BT.

    A fir, 12" dia. bears N.38°W., 40 lks. mkd: T28S R1W S4 BT

Douglas Co. Surveyors Office - Gregory E. Quibell - Gary L Langlitz - 6/24/1975 - C.S. File 57/30-14

-----

Found - A stone 12"x10"x5" (Rec. 15"x10"x5") buried in debris, marked with 5 notches on the south edge & 4 notches on the east edge (Rec. 3 notches) from which:

    An orig. 12" now 15" red cedar bears N.41°E., 14.5 ft. scribe marks visible through small unhealed opening.

    An orig. 14" now 19" D.Fir bears S.45°E., 21.8 ft. (rec. S.50°E., 21.8 ft.) alive & well healed.

    An orig. 12" now 13" D.Fir bears S.48°W., 25.7 ft. alive & well healed.

    An orig. 12" now 18" D.Fir bears N.38°W., 26.4 ft. alive & well healed.

Set - At the corner point we set a 1"x30" iron pipe with brass cap attached, mkd

	T28S
COUNTY SURVEYORS OFFICE	S 4   S 3
1975	S 9   S 10
	R1W

We place the orig. corner stone alongside the brass cap.  
Comp. decl. 20° East.