

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for secs. 3 & 4 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5400)

Set a basalt stone 12x8x8 ins., 8" in ground for closing cor. of secs. 3 and 4, marked C C on S. and 3 notches on E. and W. edges; from which

A Fir 10" dia., bears S.60°E., 18 lks. dist. mkd. T28S R1W S3 BT.

A Cedar 12" dia., bears S.12°W., 32 lks. dist. mkd. T28S R1W S4 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 24, 1969 - C.S. File 54/94-55

Found - 12x8x8 stone at closing corner mkd. "CC" & 3 notches on E and W. sides.

10" now 15" Fir S.60°E., 11.9 ft., shows good scar.

12" now 17" Cedar S.12°W., 21.1 ft., scribe visible "4".

Set Brass cap at cor. mkd: County Surveyors Office

T27S
T28S R1W CC $\frac{34}{S\ 4\ |S\ 3}$
1969

Bearing trees OK and tagged.

Douglas Co. Surveyors Office - Gary Langlitz; P. Earle, crew June 24, 1974 - C.S. File 56/51-24

Found - Orig. 12" now 17" Red Cedar with scribing visible on opened face.

Orig. SW. BT, a Fir, is now gone.

The DCSO brass cap set in 1969, has been destroyed in logging operations.

Set Brass cap at cor. mkd: County Surveyors Office 1974

T 27 S
 $\frac{S\ 34}{S\ 4\ |S\ 3}$ R
C C W
T 28 S

At record measurements from the only remaining BT, a 12' now 17" R.Cedar bearing S.12°W., 21.1 ft., We mark the following BT:

A 17" Hemlock bears S.77°E., 194.6 ft. scribed "CC T28S R1W S3 CS BT."