

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 439700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 34 only, T27-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by S.C. Flint, Contract #473, dated June 5, 1883
-(DCSO records Vol. 11 Page(s) 4769)

Set post 48x4 ins., firmly in the ground for stan. ¼ sec.
cor. marked S C on N. and S. faces, from which
A Fir 15" dia., bears N.15°E., 19 lks. dist. mkd. S C ¼ S
BT.
An Alder 14" dia., bears S.20°E., 15 lks. dist. mkd. S C
¼ S BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4775)

(36.12 chs.)
Old ¼ cor. on line which I destroy.
(40.00 chs.)
Set a Hemlock post 3 ft. long, 3" sq., 24" in the ground for
stan. ¼ cor. marked S C ¼ S34 on N. face and 3 on S. face,
from which
A Fir 30" dia., bears N.7°E., 36 lks. dist. mkd. S C ¼ S34
BT.
A Hemlock 12" dia., bears S.8°E., 12 lks. dist. mkd. S C
¼ S3 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Dec. 12, 1969 - C.S. File 54/94-85

Found - 30" now 47" D.Fir N.7°E., 23.8 ft. opened for scribe
"BT" and other marks.
No trace of SE BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 27 S R 1 W
¼ S 34
T 28 S
1969

New BT - 10" Hemlock N.77°E., 20.4 ft. mkd. ¼ S34 CS BT.