

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5364)

Set a basalt stone 20x10x6 ins., 15" in ground for ¼ sec. cor. marked ¼ on N. face; from which

- A Fir 24" dia., bears N.38°E., 42 lks. dist. mkd. ¼ S34 BT
- A Fir 24" dia., bears S.75°E., 23 lks. dist. mkd. ¼ S3 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6150-51)

Intersect the old ¼ sec. cor., which is a basalt stone, 5x10x6 ins., above ground, firmly set, marked ¼ on N. face, and witnessed as described by the surveyor general. I obliterate marks on the old SE. bearing tree, change this cor. to refer to sec. 34 only, and mark a new tree as follows:

- A Fir 26" dia., bears N.38°E., 42 lks. dist., marked ¼ S34 BT. (Old BT)
- A Fir 26" dia., bears N.24°W., 73 lks. dist. marked ¼ S34 BT. (New BT)