

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5397)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 12" dia., bears S.60°W., 60 lks., mkd: ¼ S15 BT.

A fir, 40" dia., bears N.9°W., 87 lks., mkd: ¼ S10 BT.

Maurice E Farr - U.S. Forest Service - Aug. 1983 - C.S. 62/10-1

Found - 12"x10x6" stone set 8" in the ground with marks "¼" faintly visible on north face.

Orig. BT, a 40" D.Fir snag, N.9°W., 58.2 ft. with scribe mkd "¼S" visible on decayed blaze.

Set - At position of corner stone, I set a 2½"x30" iron post with 2½" brass cap, 16" in the ground with a 3 ft dia. mound of stone up to brass cap. Cap mkd: T28S R1W ¼ S10 S15 1983.

Original stone buried alongside.

New BTs- 10" D.Fir, S.14°W., 15.7 ft. scribed "¼ S15 BT" on a single blaze.

A 12" D.Fir, N.51°W., 12.6 ft. scribed "¼ S10 BT" on a single blaze.

Magnetic declination was 18°E.