

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 479700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T27-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4769-70)

-----  
Set post 48x4 ins., firmly in the ground for stan. cor. to  
secs. 34 & 35 marked S C T27S R1W on N.; S35 on E. and S34 on  
W. faces with 2 notches on E. and 4 on W. edges, from which  
A Laurel 10" dia., bears N.50°W., 66 lks. dist. mkd. T27S  
R1W S34 BT.  
A Laurel 6" dia., bears N.85°E., 9 lks. dist. mkd. T27S  
R1W S35 BT.  
A Fir 6" dia., bears S.5°E., 20 lks. dist. mkd. S BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4774)

-----  
(77.12 chs.)  
Old sec. cor. on line which I destroy.  
(80.00 chs.)  
Set a basalt stone 12x12x6 ins., 8" in ground for stan. cor.  
of secs. 34 & 35 marked S C on N. and with 2 grooves on E.  
and 4 grooves on W. faces, from which  
A Fir 14" dia., bears N.56°E., 47 lks. dist. mkd. T27S R1W  
S35 BT.  
A Fir 14" dia., bears N.30°W., 11 lks. dist. mkd. T27S R1W  
S34 BT.