

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5364)

-----  
Set a basalt stone 15x12x6 ins., 10" in ground for cor. of secs. 2, 3, 34 and 35 marked with 2 notches on E. and 4 notches on W. edges; from which  
A Fir 24" dia., bears N.30°E., 19 lks. dist. mkd. T28S R1W S35 BT.  
A Fir 24" dia., bears S.28°E., 58 lks. dist. mkd. T29S R1W S2 BT.  
A Fir 24" dia., bears S.80°W., 48 lks. dist. mkd. T29S R1W S3 BT.  
A Fir 12" dia., bears N.82°W., 67 lks. dist. mkd. T28S R1W S34 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6151)

-----  
Intersect the old cor. of secs. 2, 3, 34 and 35, which is a basalt stone 5x12x6 ins. above ground, firmly set, marked with 2 notches on E. and 4 notches on W. edge, and witnessed as follows:  
A Fir 26" dia., bears N.30°E., 19 lks. dist. mkd. T28S R1W S35 BT. (Old BT)  
A Fir 16" dia., bears N.82°W., 67 lks. dist. mkd. T28S R1W S34 BT. (Old BT)  
I change this cor. to refer to secs. 34 and 35 only, and obliterate marks on the old SE. and SW. bearing trees.