

TOWNSHIP 28 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5382)

-----

Set a basalt stone 15x10x5", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edges, from which

A fir, 10" dia. bears N.58°E., 44 lks mkd: T28S R1W S26 BT

A fir, 20" dia., bears S.E., 25 lks., mkd: T28S R1W S35 BT

A hemlock, 14" dia., bears S.24½°W., 44 lks., mkd: T28S R1W S34 BT.

A hemlock, 14" dia., bears N.82°W., 44 lks., mkd: T28S R1W S27 BT.

Bruce A. Shaner - For: Umpqua National Forest - July 15, 1963 - C.S. File 51/259

-----

Found - Original Basalt Stone, from which a  
16" D.Fir, Orig. BT. with old face, bears N.58°E  
27.7 ft. (Rec. 29.0')  
Orig. D. Fir, now blown down, bears SE. 16.5 ft.  
16" Hemlock, Orig. BT with scribes bears S.24½°W.  
27.7 ft. (Rec.29.0')  
Orig. Hemlock, now blown down, bears N.82°W. 29.0  
ft.

New BTs- 6" Yew, I scribed "S35 BT", bears S.75°E. 5.0 ft.

8" Hemlock I scribed "S27 BT" bears N.43½°W. 12.0 ft